

GOT-3128T

12.1" SVGA TFT NEMA 4X Fanless Touch Panel Computer (-20° ~ +55° C)



- | | |
|---------------------------|--------------------|
| 1. Power switch | 6. Ethernet |
| 2. Audio (Line-out) | 7. USB 2.0 x 2 |
| 3. COM 1 (RS-232/422/485) | 8. PS/2 K/B+M/S |
| 4. VGA | 9. COM 2 (RS-232) |
| 5. Ethernet | 10. COM 3 (RS-232) |

Features



- 12" SVGA (800 x 600) color TFT LCD display
- Fanless cooling system with ULV Intel® Celeron® M 1.0 GHz processor
- NEMA 4X compliant stainless front bezel
- Supports wide temperature range, from -20° to +55° C
- Anti-vibration up to 1.3G (HDD, random)
- Supports WLAN antenna (IEEE 802.11b/g) (optional)
- Over-current power protection-fuse
- Supports various mounting ways: panel, desktop, VESA, wall (optional)



Side view

Introduction

The GOT-3128T is a 12.1" fanless touch panel computer designed for food and beverage applications. With a NEMA 4X compliant stainless front bezel, the GOT-3128T also runs in a wide temperature range, from -20° to +55° C. The GOT-3128T features a modern, super slim fanless design, is equipped with a 12.1" TFT LCD, and low power consumption ULV Intel® Celeron® M 1 GHz processor. In response to customer's requests for wireless applications, the GOT-3128T has a MiniPCI slot and an optional fixed rotational WLAN antenna for wireless network connection. By just plugging in the MiniPCI WLAN card, customers have instant access wireless LAN. The GOT-3128T is suitable for the food & beverage industry, chemical factories, transportation applications, and more.

Wide-temperature (-20° ~ +55° C) supported

The GOT-3128T adopts unique extended temperature technology, with a temperature range from -20° to +55° C, with a fanless cooling system and compact design for harsh environments.

NEMA 4X compliant design

The GOT-3128T features a stainless and IP65 water-proof front bezel, so the enclosure offers total protection against falling water and is easily cleaned by high pressure water jets.

Super slim design

The GOT-3128T is a super slim fanless touch panel computer for limited space environments. This fanless touch panel computer is designed around the concept of curved lines and soft edges by incorporating a Celeron-M ULV CPU and streamlined mechanical layout.

Anti-vibration up to 1.3G

With a special vibration-resistant design patent, the GOT-3128T can work well under 1.3G (5 ~ 500Hz) in operation mode, and equipped with a 2.5" HDD.

Specifications

Front Bezel	IP65, NEMA 4X rugged protection, stainless front bezel		BIOS	Award 4Mbit with RPL/PEX LAN boot ROM, Smartview and customer CMOS backup.
LCD Panel	Display Type	12.1" SVGA TFT LCD	Storage	1 x 2.5" IDE HDD
	Brightness (cd/m ²)	450 nits		1 x CompactFlash™
	Resolution	800 x 600		255 levels, 0-255 sec.
	View Angle (H/V)	130° / 120°		Integrated Intel® 852GM GMCH
Main System	CPU	ULV Intel® Celeron® M processor 1.0 GHz	Watchdog	
	Chipset	Intel® 852GM+ICH4	Timer	
	System	1 x 200pin DDR SODIMM max. up to	Onboard	
	Memory	1GB	Graphics	

I/O Connector	2 x RS-232 (COM 2/3) 1 x RS-232/422/485 (COM 1) 1 x VGA 1 x Audio (Line-out) 1 x PS/2 keyboard/mouse 2 x USB 2.0 2 x 10/100Mbps Ethernet
Expansion Interface	1 x MiniPCI slot
Touchscreen	Resistive type
Power Supply	16~28V _{DC} , 36W, w/ fuse power protection
Dimensions	338mm (13.1") (W) x 72.4mm (2.83") (D) x 272mm (10.7") (H)
Weight (net/gross)	5.4 kg (12 lb)/7.45 kg (16.44 lb)
Environmental	Operation temperature: -20°C ~ +55°C (-4°F ~ +131°F) Relative humidity: 10% ~ 95% @40°C; non-condensing Operation vibration: 1.3G, 5 ~ 500Hz, random for 2.5" HDD 3G, 5 ~ 500Hz, random for CompactFlash™
Certification	CE

Ordering Information

GOT-3128T	12.1" SVGA TFT fanless touch panel computer with resistive T/S, stainless front bezel
82231200090E	Wall/VESA mount kit for GOT-3120T
82231200080E	Desktop stand kit for GOT-3120T
E989110036	VESA ARM wall mount type
E989110035	VESA ARM clamp type
E392203100	802.11 b/g wireless LAN kit
50966A23020E	Power adapter, 72W, 110~230V _{AC} to 24V _{DC}

*Specifications and certifications are limited to optional.

Optional EOS Installation

Windows® XP Embedded
Windows® CE.NET

Optional OS Installation

Windows® 2000
Windows® XP
Linux Kernel 2.6

Touch Panel Computers for Various Industry Applications

Digital Signage and Display Solutions

Medical Panel Computers

Medical Grade Monitors

GOT Fanless Touch Panel Computers

Touch Panel Computers for Infotainment

Touch Panel Computers for Automation

Touch Panel Monitors for Automation

Touch Panel Computers with HMI Software

Dimensions

