
PANELI 173-841

17"TFT Expandable Intel® Core™2 Duo Industrial Panel Computer with 2 PCI Slots





- 1. COM 1 (RS-232/422/485)
- 2. DVI-I
- 3. Ethernet x 2
- 4. IEEE 1394a x 2
- 5. USB 2.0 x 4
- 6. Audio (Mic-in/Line-out)

9. AC power

10. PCI slot x 2

- 7. COM 2/3 (RS-232)
- 8. Power switch

Features



- ▶ 17" SXGA TFT LCD display
- ► Intel® Core™2 Duo processor
- ▶ Industrial-grade material front bezel: anti-corrosion
- ► Intel® Q965+ICH8 chipset
- ► Supports 2 PCI slots
- ▶ Built-in speakers & optional WLAN module
- ▶ Windows® Vista supported
- ▶ Panel/Rack mounting ways



Side view

Introduction

The PANEL1173-841 is a 17" Industrial panel PC which features Intel® Core™2 Duo processor and Intel® Q965 chipset to provide powerful computing performance. This panel PC also offers the expansion ability with 2 PCI slots. Further, the PANEL1173-841 adopts built-in speaker and WLAN module for wireless connectivity.

Powerful computing: Intel® Core™2 Duo processor
The PANEL1173-841 features Intel® Core™2 Duo with maximum FSB 1066 MHz and Intel® Q965+ICH8 chipset. It features two IEEE 1394a ports, two gigabit Ethernet and up to 4GB of dual-channel DDR2 system memory which deliver high computing capability for high performance-demanding applications.

Expandable for 2 PCI slots

The PANEL1173-841 has 2 PCI slots for expansion purpose. User can easily plug in standard half-size PCI cards such as motion card, communication card and so on.

Speaker & WLAN antenna supported

The PANEL1173-841 features built-in speaker, optional WLAN module and antenna for wireless network connectivity.

Specifications

Front Bezel	Industrial-grade material with IP65/NEMA 4 rugged protection	
LCD Panel	Display Type	17" SXGA TFT
	Brightness (cd/m²)	260 nits
	Resolution	1280 x 1024 pixels
	View Angle (H/V)	120°/140°
Main system	Main board	SBC86841
	CPU	LGA775 for Intel® Core™2 Duo / Core™ Solo processor with FSB 533/667/800/1066 MHz

	Chipset	Intel® Q965+ICH8
	System Memory	2 x 240-pin DDR2 DIMM max. up to 4GB
	BIOS	Phoenix-Award 4Mbit with RPL/PXE LAN Boot ROM, SmartView and Customer CMOS Backup
	Storage	2 x 3.5" or 2 x 2.5" SATA HDD
	Drive	1 x slim CD-ROM
	Watchdog Timer	255 levels, 1~255 sec.

IO connector	2 x RS-232 (COM 2/3)
	1 x RS-232/422/485 (COM 1)
	2 x IEEE 1394a
	4 x USB 2.0
	2 x PS/2 keyboard/mouse
	2 x 10/100/1000Mbps Ethernet
	1 x DVI-I(female) for display
	(attached with a converter for DVI-I to VGA)
	1 x Audio (Mic-in/Line-out)
Expansion	2 x PCI slot
Interface	
Touch screen	Resistive type
	Light Transmission 79%
	1 million activations (typical) at a single point
Power supply	100 ~ 240Vac, 250W
Dimensions	450mm (17.71") (W) x 150mm (5.9") (D) x
	370mm (14.56") (H)
Weight (net/gross)	7.5 kg (16.5 lb)/11.3 kg (24.9 lb)
Environmental	Operation temperature: 0°~40°C (32°~104°F)
	Relative humidity: 10-95%@40°C, non-condensing
	Operation vibration: 1.0G,5~500Hz, random
Certification	CE

Optional Accessories

82211730040E	2 x 3.5" HDD kit
82011750130E	2 x 2.5" HDD kit
82011750110E	Rack mount kit
82211780050E	Wireless LAN kit
82011756110E	17" rack mount kit

Optional OS Installation

Windows® 2000/XP/Vista

Integrated Solutions for Automation

SCADA

Total Solution for Vertical Markets

GOT Fanless Touch Panel Computers

PANEL1000 Industrial Panel Computers

PANEL6000 Industrial Flat Panel Monitors

Embedded Field Controllers

Industrial Networking

& Control Cards

Ordering Information

PANEL1173-841-R 17" TFT Intel® Core™2 Duo panel PC with 2 PCI slots

*Specifications and certifications are limited to optional.

Dimensions

